

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/048832 A1

(51) International Patent Classification⁷: **F16L 3/10**

Arthur [AU/AU]; 17 Marlborough Avenue, Harbord, New South Wales 2096 (AU).

(21) International Application Number:
PCT/AU2003/001565

(74) Agents: SMEETON, Anthony, Richard et al.; DAVIES COLLISON CAVE, Level 10, 10 Barrack Street, Sydney, New South Wales 2000 (AU).

(22) International Filing Date:
21 November 2003 (21.11.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002952900 25 November 2002 (25.11.2002) AU

(71) Applicant (*for all designated States except US*): VSL PRESTRESSING (AUST) PTY LTD [AU/AU]; 6 Pioneer Avenue, Thornleigh, New South Wales 2120 (AU).


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): CAVILL, Brian,

[Continued on next page]

(54) Title: PROTECTIVE DEVICE



(57) Abstract: A protective device (10) for use in the protection of at least a portion of an elongated article (50) which includes a main body (12), first and second parts (22), (27) which are connectible together such that, in an assembled position the main body has a chamber therein (14). The first and second parts each have two longitudinal extending side edge portions (23), (28), respective side edge portions of the first part being adapted to cooperate with the respective side edge portions of the second part to connect the two parts together in the assembled position.

WO 2004/048832 A1